



#### • Instructions for inbuilt controller 內建控制板說明:

1. Make sure ①、②、⑨ are well connected.  
先確認 ①、②、⑨ 端子位置皆連接正確
2. Connect the fan ARGB connectors with ③~⑧  
連接ARGB風扇訊號線 ③~⑧ 位置
3. Connect SATA Connector with ⑨  
連接 ⑨ SATA電源
4. Press the Power button on the case.  
開啟機箱Power按鍵
5. Press the LED mode button on the I/O port; enjoy more than 13 light effects.  
操作I/O上LED控制按鍵，超過13種以上燈效模式

#### • If you would like it to work in sync with the motherboard, please connect ① the 3-pin connector with the motherboard.

如需與主板ARGB同步操作，請將 ① 3pin接線連接至主機板

1. Long press the LED button for 3-6 seconds and wait for white light blinking twice, and it will change to motherboard sync mode.  
長按I/O上LED控制按鍵3~6秒，待連續兩次白光閃爍時，將會切換至與主板同步模式。
2. If you would like to use the LED button on the I/O port, slightly press it, and it will return to the inbuilt controller mode.  
如欲切回機殼內建燈光控制板，請至I/O上輕按LED控制按鍵，將回到機殼內建燈光控制板燈效模式。
3. If you press the LED button for more than 6 seconds, the light effects will be turned off after the white light blinks 4 times. Press the LED button again, and it will return to the inbuilt controller mode.  
如長按I/O上LED控制按鍵大於6秒，LED將會在4次白光閃爍後自動關閉燈光，再按一次I/O上LED控制按鍵則恢復內建燈光模式。