



XPG LEVANTE 360 ADDRESSABLE RGB CPU COOLER

An All-In-One CPU Liquid Cooler with industry-leading solution from Asetek, made for heat control and stable CPU performance. Designed with a 360mm-Radiator, 4-Pin PWM Control Mode and fine-tuned with dazzling ARGB Fans and lighting effects at the water pump, manageable by an included external ARGB Controller.

HIGH PERFORMANCE All-in-One CPU LIQUID COOLING

XPG LEVANTE 360 Addressable RGB CPU Liquid Cooler offers superb cooling capability in stabilizing CPU temperature and maintaining CPU proper functioning. ARGB lighting effects create additional gaming atmosphere.



Asetek's PATENTED COOLING SOLUTION


XPG LEVANTE 360 Addressable RGB CPU Cooler utilizes Asetek's latest cooling solution to ensure CPU temperature management is at the highest efficiency performance. Its thermal-optimized copper plate with 0.15mm-thin micro channel provide large cooling area and boosting heat exchange efficiency.





EFFICIENT COOLING SOLUTION

XPG LEVANTE 360's three Vibrant Dual Ring 120mm ARGB fans have 20 ARGB LEDs each. PWM Fan with Fluid Dynamic Bearing (FDB) fans are designed with auto-restart mechanism (up to 40,000 hours at 40°C of MTBF).



EXTERNAL ARGB CONTROLLER

XPG LEVANTE 360 AIO CPU LIQUID Cooler's external ARGB Controller allows users to switch Mode, Speed and Light functions of both the ARGB Fans and the Water Pump.



Features

- Reliable high performance CPU Liquid Cooler with Asetek's Cooling Solution.
- External ARGB Controller for the fans and the water pump.
- 3 Vibrant Dual-Ring 120mm ARGB Fans.
- Fluid Dynamic Bearing (FDB) fans with 4-Pin PWM design.
- ARGB lighting for the water block and fans.
- Large surface 360mm all aluminum radiator.
- All-in-One hassle-free installation, no additional setup required.



Specifications

WATER PUMP		FAN SPECIFICATIONS	
Water Pump Dimension	86 x 72 x 36 mm	Fan Size	120mm ARGB
Water Pump Material	Dual Bearings	Fan Bearing Type	Fluid Dynamic Bearing
Control Mode	PWM	Fan Speed	600 ~ 2000 RPM
CPU Socket Support		Fan Air Flow	61.5 CFM
Intel	LGA 115x, 1200, 1366, 2011, 2066	Fan Noise	34.0 db(A)
AMD	AM4, TR4 (TR4 bracket not included)	Fan Dimension	120 x 120 x 25mm
Thermal Grease	Pre-Applied	Fan Static Pressure	1.42mm-H ₂ O
		Control Mode	PWM
		Protection	Auto-Restart

RADIATOR

Radiator Dimension	394 x 120 x 27mm
Radiator Material	Aluminum
Tube	400mm Sleeved Rubber Tube

Ordering Information





Packaging Contents



PACKAGE CONTENTS

x1	CPU Liquid Cooler
x1	ARGB LED Lighting Controller
x3	Vibrant Dual-Ring 120mm ARGB Fan
x3	Cable: Fan Power
x3	Cable: ARGB 3-Pin
x12	Screws: Fan
x12	Screws: Radiator
x12	Washers
x4	Thumbscrew Caps
x1	Backplate (Intel CPUs)

PACKAGE CONTENTS: MOUNTING Intel CPUs

x2	Double-sided Foam Tape
x1	Intel Mounting Bracket
x4	Intel LGA 1200 / 1366 / 115X Standoff Screws
x4	Intel LGA 2066 / 2011 Standoff Screws

PACKAGE CONTENTS: MOUNTING AMD CPUs

x4	AM4 Standoff Screws
x1	AMD AM4 Mounting Bracket
	(AMD TR4 Threadripper bracket not included)